




























Function	Signal*	Model No.	Description	Picture	Application	Output Drive Distance	Size/ Mounting*
QikConnect kits (pack)	VGA/Component	TPY311	Transmitter-Receiver Pair		Connect a PC to a projector or plasma without power at the transmitter.	200-ft (60m)	Ultra Compact
		TPY312	Transmitter-Receiver Pair		Connect a PC to a projector or plasma without power at the transmitter.	330-ft (100m)	Compact
		TPY315	CAT5 Transmitter/Receiver		Basic computer video extender pair.	500-ft (150m)	
		TPY317	AV Extenders		For longer cable runs of computer video.	1000-ft (330m)	
	VGA/Component + Audio	TPY321	UTP Extender Pair for Video + Audio		Connect a centrally located source to remote displays.	500-ft (150m)	
	Composite/Component + Audio	TPC341	CAT5 Transmitter/Receiver		Connect a DVD player to a Plasma up to 500-ft away.		
	VGA/Component + Audio	TPY351	Transmitter-Receiver Pair		Basic computer AV extender pair.		
Twisted-Pair Transmitters	VGA/Component	TTY111	CAT5 Transmitter		Send computer video to a projector.	200-ft (60m)	
		TTY115	UTP Extender Transmitter		Transmitter computer video up to 1000-ft.	1000-ft (330m)	Compact / Rack
	VGA/Component + Audio	TTY121	CAT5 Transmitter		For transmitting computer video over long cable runs.		
	Composite/Component + Audio	TTC141	AV Extender Transmitter		Send component video to a HDTV.	500-ft (150m)	Compact
	VGA/Component + Audio	TTY134	1x4 CAT5 Transmitter		Distribute computer video + audio to up to 4 LCDs, Plasmas, or Projectors	1000-ft (330m)	Rack
		TTY138	1x8 UTP Extender Transmitter		Send VGA to up to 8 displays.		
		TTY155	5 Pack AV Extender Transmitter		Send 5 channels of computer video + audio to 5 remote displays.		
Twisted-Pair Receivers	VGA/Component	TRY211	UTP Extender Receiver		Receive computer video on a projector.	200-ft (60m)	Ultra Compact
		TRY215	CAT5 Receiver		Receive component video on a plasma.	500-ft (150m)	Compact
		TRY216	Dual Output CAT5 Receiver		Receive computer video on 2 displays.		
		TRY315	CAT5 Receiver		Receive video over long cable run.	1000-ft (330m)	
		TRY316	Dual Output UTP Extender Receiver		Receive computer video and display on 2 Plasmas.		
		TRY319	CAT5 Receiver w/ Repeater		Receive and display and then daisy chain with another receiver.		
	VGA/Component + Audio	TRY221	AV Extender Receiver		Receive computer video with audio on an LCD up to 500-ft away from its source.	500-ft (150m)	
		TRY222	Dual Output CAT5 Receiver		Receive computer video + audio on 2 displays.		
		TRY229	UTP Extender for Video + Audio w/ Repeater		Receive and display video + audio and then daisy chain with another receiver.		
		TRY251	AV Extender Receiver		Receive computer video with audio on an LCD over longer cable runs.	1000-ft (330m)	
		TRY252	Dual Output CAT5 Receiver		Show computer video + audio on 2 displays.		
		TRY259	UTP Extender for Video + Audio w/ Repeater		Receive and display video + audio and then daisy chain with another receiver at great distances.		
Composite/Component + Audio	TRC241	AV Extender Receiver		Receive component video + audio and display on a HDTV up to 500-ft away.	500-ft (150m)		

\* For Component video connection of YPbPr signal (SD/HD) adapter cable from HD-15 to 3-RCA is required[MP] . This cable is [MP] an available optional accessory & Ultra-Mount sized transmitter is attached directly to source HD-15 like cable connector. Receiver are semi-compact and are mounted next to display or its mount. Compact sized transmitter are attached to furniture, source or in rack using shelf, while receivers are mounted next to display or its mount.